



Bearing No. RS-5038

| | |
|-------------------------------|------------------|
| Size | 190x290x136 mm |
| Bore Diameter | 190 mm |
| Outer Diameter | 290 mm |
| Width | 136 mm |
| d | 190 mm |
| D | 290 mm |
| B | 136 mm |
| C | 135 mm |
| r min. | 1,1 mm |
| C2 | 1,3 mm |
| Weight | 32 Kg |
| Basic dynamic load rating (C) | 1120 kN |
| Basic static load rating (C0) | 2230 kN |
| hidYobi | RS-5038 |
| LangID | 1 |
| D_ | 290 |
| B_ | 136 |
| hidTable | ecat_NSCLDRSG |
| Cx | 1.3 |
| mass | 32 |
| GRS rpm | 500 |
| da_min | 197 |
| C0 | 2230 |
| DE_ | 267 |
| Prod_Type3 | CRB_FRFS_PT_WOLR |
| DA_ | 26 |
| Z_ | 29 |
| r_min | 1.1 |
| yobi | RS-5038 |

| | |
|---------|------------------------------------|
| SDM_ | 241 |
| r | 135 |
| KBRG | 4220 |
| DI_ | 215 |
| calcUrl | /BearingGuide/html/calculation.jsp |
| doh | 6 |